

# TC 155

## Nonferrous Corrosion Inhibitor

TRIM<sup>®</sup> TC 155 is a nonferrous corrosion inhibitor for use in water soluble and straight oil systems. It is particularly effective in preventing staining and white rust on die cast alloys containing copper.

### Additives



#### The troubleshooters:

*As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM<sup>®</sup> tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilise the emulsion, and replenish dye.*

*Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.*



#### Choose TC 155:

- Prevents staining and white rust on die cast alloys containing copper
- Nonferrous corrosion inhibition

#### TC 155 especially for:

**Applications** — corrosion inhibition

#### Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions or from your Master Fluid Solutions' Authorised Distributor.

# TC 155

## Nonferrous Corrosion Inhibitor



### Application Guidelines

- TC 155 is added at a rate of 0.05%-0.125% to working solutions.
- This product should not be used in conjunction with systems containing copper or copper amine compounds as part of their formulation or systems to which these compounds have been added.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.2trim.us/distributors.php>, your District Sales Manager, or call our Tech Line at +49 211 77 92 85 - 13.

### Physical Properties Typical Data

Colour (Concentrate)	Amber
Odour (Concentrate)	Mild
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 100°C

### Ordering Information


2-quart tip "N" measure®  
20-litre pail


TRIM® TC 155 | ©1965-2020 Master Fluid Solutions™ | 2020-05-28


### Additional Information


- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:


[https://2trim.us/di/?plr=TC155\\*en\\*eu](https://2trim.us/di/?plr=TC155*en*eu)



 Hasselsstraße 6-14  
Düsseldorf, 40597  
Germany

 +49 211 77 92 85 - 0

 [info-eu@masterfluidsolutions.com](mailto:info-eu@masterfluidsolutions.com)

 [masterfluidsolutions.com/eu/en/](https://www.masterfluidsolutions.com/eu/en/)

