

WEDOLiT AN 7324

Special-Fluid 100°C flash point

(aromatic content \leq 2%)



WEDOLiT AN 7324 is a leading edge corrosion inhibitor for steel and other metals. It can be applied by spraying, flooding, brushing or rolling on parts with surface temperatures \leq 80°C. This results in time savings and enhances productivity.

WEDOLiT AN 7324 fulfills all requirements regarding Altautorichtlinie 2000/53/EG. It is not subject to the German VOC-regulation (VOC-guideline, 31. BImSchV) nor to the Swiss regulation for VOC (Lenkungsabgabe VOCV Swiss).



Choose WEDOLiT AN 7324:

- Parts with surface temperatures \leq 80°C can be treated without odour formation or a loss in performance
- Suitable for VCI foils
- Stable against acidic and alkaline impurities
- Good material compatibility
- Easily removable with organic solvents (cold cleaners) or water-miscible alkaline industrial cleaners
- Water displacing with a very good wetting behaviour

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Medium-brown, turbid-clear	Visual
Density at 15°C:	0.83 g/cm ³	ASTM D 7042
Viscosity at 20°C:	20.5 mm ² /s	ASTM D 7042
Flash point:	> 160 °C	DIN EN ISO 2719
Film weight:	1.7 g/m ²	Dipping procedure
Film type:	Oily	Haptical
Dewatering effect:	< 70 s	Internal test method
Water separation:	None	Internal test method
Humidity test:	70 cycles	DIN EN ISO 6270-2 AHT
Salt spray performance:	12 h	DIN EN ISO 9227 NSS

Application Guidelines

Storage must be frost-free between 5 - 35°C.

The minimum durability is 12 months in an original sealed package.


Additional Information


The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=AN-7324*en*eu


WEDOLiT AN 7324

©2019-2020 Master Fluid Solutions™ | 2020-08-12

 Hasselsstraße 6-14
Düsseldorf, 40597
Germany

 +49 211 77 92 85 - 0

 info-eu@masterfluidsolutions.com

 masterfluidsolutions.com/eu/en/

